


# UNIPEX GLOBAL CO., LTD.

3G09-11, No. 5, Sec. 5, Hsin Yi Road, Taipei City, 11011, Taiwan

TEL: 8862-66173338

FAX: 8862-66209887

## Testing Report

ARTICLE NAME	1501 PE Adhesive tape			
PRODUCTION CONSTRUCTION	 <ul style="list-style-type: none"> <li>→ Acrylic adhesive (40u)</li> <li>→ 1501 PE</li> <li>→ Acrylic adhesive (40u)</li> <li>→ 80g glass paper</li> </ul>			
SUBSTRATE		LINER		
ARTICLE NAME	1501 PE	ARTICLE NAME	80g glassine paper	
THICKNESS (mm)	1mm±0.2mm	THICKNESS (u)	80±5u	
BASIC WEIGHT (g/m <sup>2</sup> )	0.066g/m <sup>3</sup>	BASIC WEIGHT (g/m <sup>2</sup> )	80±3g	
COLOR	white	COLOR	white	
SMOOTHNESS	GOOD	SMOOTHNESS	GOOD	
PRINT ABILITY	GOOD	DIE CUTTING	GOOD	
PRESSURE SENSITIVE ADHESIVE				
ADHESIVE	7005			
THICKNESS	80u	HOLDING POWER (hr/kg*25mm)	720(hr)	
DRY COATING WEIGHT	220g/m <sup>2</sup>	WERTHER RESISTANCE	GOOD	
SOVLENT RETENTION (wt%)	/	TEMPERATUR E RANGE (°C)	-20°C~100°C	
(NO/BALL) INITIAL TACK	13#	HUMIDITY RANGE (%)	0%-95%. H	
180° PEEL ADHESIVE (kgf/25mm)	1.0kgf/25mm	SOLVENT RESISTANCE	GOOD	
STORAGE CONDITION	Good advise: Storage to indoor temperature 25±2°C relative humidity 50 %-70%RH of the environment.			