

TEST REPORT

NUMBER: STH0602016

DATE: JAN 18, 2011

SAMPLE DESCRIPTION:

FOUR (4) PIECES OF SUBMITTED SAMPLE SAID TO BE:

ITEM NAME: POWER TACK.

TESTED COMPONENT OF

GOODS EXPORTED TO: EUROPE, U.S.A. & JAPAN.

COUNTRY OF ORIGIN: CHINA.

TESTS CONDUCTED:

AS REQUESTED BY THE APPLICANT, FOR DETAILS REFER TO ATTACHED PAGE(S)

CONCLUSION:

TESTED SAMPLES STANDARD

STANDARD RESULT EN71 PART 3: 1994 AND PASS

SUBMITTED SAMPLE AMENDMENT A1 : 2000

TO BE CONTINUED

PREPARED AND CHECKED BY: FOR INTERTEK TESTING SERVICES LTD., SHANGHAI AUTHORIZED BY: FOR INTERTEK TESTING SERVICES LTD., SHANGHAI

GALE GAO CHEMICAL DIVISION MANAGER JAMES WANG GENERAL MANAGER

Page 1 of 2

1/F., No. 4 Building, Shanghai Comalong Industrial Park, 889 Yishan Road, Shanghai, China. 上海 宣北 \$889 号 乔永 正 北 地 号 传 1 是 Tel: 0086-21-6120 6565, Fax: 0086-21-6495 0740 Postcode: 200233 Attention is drawn to the terms and conditions printed overlant.



NUMBER: STH0602016

TOXIC ELEMENTS ANALYSIS

AS PER EUROPEAN STANDARD ON SAFETY OF TOYS EN71 PART 3: 1994 AND AMENDMENT A1: 2000, ACID EXTRACTION METHOD WAS USED AND TOXIC ELEMENTS CONTENT WERE DETERMINED BY INDUCTIVELY COUPLED ARGON PLASMA SPECTROMETRY.

	RESULT IN mg/kg	LIMIT mg/kg
SOL. BARIUM (Ba)	<5	250
SOL. LEAD (Pb)	<5	90
SOL. CADMIUM (Cd)	<5	50
SOL. ANTIMONY (Sb)	<5	60
SOL. SELENIUM (Se)	<5	500
SOL. CHROMIUM (Cr)	<5	25
SOL. MERCURY (Hg)	<5	25
SOL. ARSENIC (As)	<2.5	25

mg/kg = MILLIGRAM PER KILOGRAM

SOL. = SOLUBLE

< = LESS THAN

TESTED COMPONENT: SOFT ADHESIVE CLAY IN GREY WHITE COLOR.

DATE SAMPLE RECEIVED : JAN.17, 2011

TESTING PERIOD : JAN.17, 2011 TO JAN.18, 2011

END OF REPORT

Material Safety Data Sheet

Product Name:

POWER TACK

Not classified as hazardous according to criteria of NOHSC

COMPANY DETAILS

Company Name:

NINGBO MR STATIONERY I/E CO.,LTD

Address:

Floor 20, XinZhouYinZuo Building,No.88 QianHe Nan

road, Yin Zhou Ningbo, China 315100

Tel/Fax:

Tel: 0086 574 27869307

IDENTIFICATION

Product Name Proper Shipping

Name

POWER TACK

None Allocated

None Allocated

UN Number
DG Class
Packing Group
Hazchem Code
Poisons Schedule

None Allocated None Allocated None Allocated Not Scheduled

Product Use

A multi-purpose, oil based synthetic rubber adhesive.

Physical Data

Appearance Pale blue, tacky, mouldable putty like adhesive with neglgible

odour.

Melting Point Boiling Point Vapour Pressure Specific Gravity

Not Available Not Available 1.97 g/cm3

Not Available

Flash Point Flamm, Limit LEL Not Available Not Applicable

Other Properties

Other Information Solubility in Water (g/L): Insoluble

Ingredients

Ingredients

Name Mineral fillers CAS

Proportion 60-100 %

Mineral Oil	1-10 %
Hydrocarbon polymers	1-10 %
Piament	0-1 %

HEALTH HAZARD INFORMATION

Health Effects

Acute - Swallowed

Acute - Eye Acute - Skin

Acute - Inhaled Chronic

Practically non-harmful.

Practically non-harmful. Practically non-harmful.

Not Applicable None known.

First Aid

Swallowed Not expected to be a problem. However, should discomfort occur,

seek medical advice.

Eye Not a likely hazard. However, should it occur flush with plenty of

water. Seek medical attention if irritation occurs.

Skin Wash affected area with soap and water.

Inhaled Not a likely hazard.

Advice to Doctor

Advice to Doctor Treat symptomatically.

Other Health Hazard Information

PRECAUTIONS FOR USE

Exposure Limits No exposure standard is available for the material as such. An

exposure standard is not applicable to this product as it is

practically non-harmfulvia all routes of exposure.

Natural ventilation sufficient for normal use. **Eng. Controls**

Personal Protection

Protective Equip. Respiratory protection not required for normal use.

Safety glasses not necessary for normal use. Protective gloves not necessary for normal use.

Flammability

Fire Hazards Non Flammable

SAFE HANDLING INFORMATION

Storage and Transport

Storage and **Transport**

Store away from heat, strong oxidising agents and acids.

Proper Shipping Name

None Allocated

Spills and Disposal

Spills & Disposal

Collect spilled material by sweeping up and placing in suitably

marked containers for either recycling or disposal.

Fire/Explosion Hazard

Fire/Explos.

Hazard

Hazardous decomposition products on burning: oxides of carbon, smoke and fumes. Fire-fighting personnel should wear respiratory protection. Extinguishing Media: Foam, dry chemical and carbon

dioxide.

Hazardous Reaction

Incompatible with strong oxidising agents and acids.

Hazchem Code

None Allocated

OTHER INFORMATION

Toxicology

No data available.

Pkg. & Labelling

No special packaging required.

Technical Data

Refer Product Information Bulletin

User Codes User Code Field 2 SEE PAGE 1 Other Information

N/A - Not Applicable

CONTACT POINT

Contact

NINGBO MR STATIONERY I/E CO.,LTD

Floor 20, XinZhouYinZuo Building, No. 88 QianHe Nan road, YinZhou

Ningbo, China 315100

Tel: 0086 574 27869307

...End Of MSDS...

